

DM100i™

מכונת ביול מהמובילות בעולם

- אמינות ללא תחרות
- משקל אינטגרלי כחלק מהמכונה
- קצב הזנת מעטפות: כ-30 מכתבים בדקה בהזנה ידנית
- הזנת מעטפות חצי-אוטומטית
- הדפסה שקטה במיוחד לסביבת משרד
- ממשק עבודה נוח ובשפה העברית
- חיבור לדואר ישראל לביול שוטף ולתעריפים מעודכנים



DM100i™ Digital Mailing System



DM100i™ Digital Mailing System

Designed with flexibility in mind, the DM100i™, powered by Pitney Bowes' IntelliLink™ technology represents the ultimate answer to the mailing needs of busy businesses. The latest digital technology makes processing mail quiet and efficient - the perfect office companion.

Future-proof mailing

IntelliLink™ connects Pitney Bowes' DM100i™ to a secure server, via the Internet, enabling services such as postal tariff changes, software updates and advertising slogans to be downloaded quickly and effortlessly.

Correct value postage - every letter, every time

The DM100i™ incorporates a 2.5kg integral weighing platform, freeing up desk space and guaranteeing that each letter or package bears the correct postage value.

Fast, accurate postage re-crediting

Replenish your meter 24-hours a day with simple one-touch refills via - **POSTAGE BY PHONE** quick, secure and hassle-free. Get up to 55 days free credit with Purchase Power post now, pay later facility.

Easy to use

All controls are fully integrated on one clear control panel with user-friendly instructions to guide the operator through each stage of processing mail.

Streamlined processing

Efficiently frank and mail pieces up to 9.5mm thick, whilst larger mail is quickly processed with self adhesive tape strips. Mailing couldn't be simpler with up to 5 presets for your most commonly used jobs.

Strengthen your brand

Enhance and build your corporate identity by transforming standard envelopes into eye-catching branded mail pieces.

DM100i™ Specifications

» Physical dimensions

Length	345mm
Depth	400mm
Height	230mm
Weight	6.8 kg approximate

» Speed

Up to 30 letters per minute

» Material sizes

Minimum material size	76mm x 127mm
Maximum material size	330mm x 381mm
Material thickness	9.5mm (max) to 0.18mm (min)
Envelope flap depth for sealing	76 (max) to 22mm (min)

» Standard operating features

Slogan and town circle download (by modem)
2.5kg integrated weighing platform
Auto-dating
Low postage warning
High value protection
Original value resetting
Low ink warning
Password security
PC interface
5 job presets

» Electrical

100-240 V, 50/60 Hz, 3A

» Noise

55dB

» Connectivity requirements

Connects to a standard analog phone line

Pitney Bowes Limited Limited

Elizabeth Way, Harlow, Essex CM19 5BD
Tel 08705 252525 • Fax 08705 449450
www.pitneybowes.co.uk

© 2004 Pitney Bowes. All rights reserved.

Specifications are subject to change without notice. Performance may vary depending on exact job configuration and environmental conditions.